Power tool Plastic tie wraps clamping





Clamping: 8 clamping levels

Low force

Tension : from 14.61 to 56.20 lbs (65 - 250 N) Tie wrap : from 0.18 to 0.30 in (4.8 - 7.6 mm)

Large tie

wraps

Battery operated



Narrow and rotative head





Weigth < 900g Reduction of MSD



Autonomy > 8h, eq. 3200 tie wraps Indicators battery/maintenance



Narrow and 360° rotative head Adjustable and repeatable clamping



Resistant to floor falls Easy maintenance

ADT Tools in videos



Alpes DEIS - 74970 Marignier - FRANCE Phone: +33 (0)4 50 89 24 00 Email: adt-sales@alpes-deis.fr

Contact

Power tool Plastic tie wraps clamping



Product information

Powered clamping tool for plastic tie wraps facilitating the **tightening** operation by its high repeatability and continuous cut. Thanks to its ergonomic design, it avoids musculoskeletal disorders (**MSD**).

The **prevention of MSD** allows you to improve the productivity and quality of work, and gives you a long-term advantage.

Already used in:













Product characteristics

Sales reference	ADT120L-PROD	GGY SAD
Dimensions (H x L x W)	200 mm (7.8 in) x 270 mm (10.6 in) x 70 mm (2.75 in)	To the second se
Head characteristics	Narrow and 360° rotative head, flush cut of the tie wrap	
Material	PA6 composite charged in glass fiber 30%, drop resistance	7
Clamping force	Adjustable: 8 levels of clamping from 14.61 to 56.20 lbs (65 - 250 N)	(Ú)
Tie wraps width	0.18 to 0.30 in (4.8 - 7.6 mm) - other widths, see <i>Product Range</i>	
Tie wraps type	Compatible with Advanced Cable Ties, HellermannTyton, ABB, Panduit, Legrand	

Usage characteristics

Usability	< 1.9 lbs (900g) (battery included) Ambidextrous tool, center of gravity in the handle
Autonomy	> 8h, equivalent to the clamping of 3200 tie wraps 3 levels battery indicator
Maintenance	Easy product maintenance (more information in the user manual)

Accessories

Rechargeable battery	Lithium-lon, 11.25V / 2.95Ah, recyclable	Co of
Battery charger	Universal : 110 - 240 Vac, 50/60Hz Available in United-States, Europe, United-Kingdom, Australia versions	
Maintenance kit	2 cutting blades, 1 ADT-120L head, 1 head disassembly tool	
ADT measure certificate	Characterization of clamping forces	Name
Suspension hook	Usable on fixed work station	

Product Range

ADT-50	Tie wraps width: 0.09 - 0.18 in (2.4 - 4.8 mm) Clamping force: 14.61 - 56.20 lbs (65 - 250 N) - 8 positions	
ADT-120	Tie wraps width: 0.18 - 0.30 in (4.8 - 7.6 mm) Clamping force: 39.34 - 66.77 lbs (175 - 297 N) - 2 positions	
ADT-120L	Tie wraps width: 0.18 - 0.30 in (4.8 - 7.6 mm) Clamping force: 14.61 - 56.20 lbs (65 - 250 N) - 8 positions	

Contact

Alpes DEIS - 74970 Marignier - FRANCE Phone : +33 (0)4 50 89 24 00 Email : adt-sales@alpes-deis.fr